



## HYDRAULIC ENGINEERING REPAIR SERVICES

# Warranty terms & Conditions for Drivetrain components

### **OFF-HIGHWAY EQUIPMENT**

Six months or 1000 hours whichever occurs first from date of delivery

### **CONDITIONS OF WARRANTY**

1. Prop-shafts to be balanced when installing new/repaired center portions, gearboxes, transmissions, torque converters or any other related components
2. Correct oil to be used in unit. Oil in off highway transmissions to be changed after the first 250 hours of operation.
3. All external filters to be replaced with new when fitting repaired/new components
4. Cooler lines to be thoroughly cleaned prior to installation of new/repaired transmissions.
5. Oil coolers to be ultrasonically cleaned prior to installation of new/repaired transmissions.
6. Storage of units to be done in a clean environment and units are to be stored in such a manor that they do to rest on a flange, valve body.
7. Units remaining in storage for a period of longer than four months are to be completely filled with oil to preserve seals and prevent corrosion
8. Units supplied are warranted against any failure related to material defect or faulty workmanship during the period of warranty as listed above

### **Warranty shall become null and void should**

1. The unit be tampered with during the warranty period
2. Any of the above conditions are not adhered to
3. Failure or breakages on the unit are related to the abuse or misuse of the equipment
4. Failure or breakage on the unit related to other faulty components in the vehicle

**Contamination is a large contributor to transmission and axle failures and HERS will not be held liable for any failures related to contaminated systems**